

# CRB Cap

## Automotive | Drivetrain | Transmission

Print Date: 2024-08-30

### Benefits

- CRB Cap is a press fitted cap on the clutch release bearing. The cap comes in contact with the diaphragm spring of the clutch when the clutch is pressed for disengaging the transmission with the engine. This cap isolates metal to metal contact of CRB flange and diaphragm spring fingers.



### Details

Isolation of metal to metal contact aids in noise reduction; Wear and durability characteristics are 3 times better in relation with competitive wear resistant grades; Uneven wear of diaphragm spring fingers is nullified, eliminating premature failure of the clutch assembly; CRB flange hardness requirement can be reduced and hardening process for the bearing flange can be eliminated

### Products

Stanyl® TW271B6  
(PA46+PTFE)-CF30

### Speciality products

Stanyl®



All the trademarks mentioned here are trademarks of Envalior.

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.

Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envalior 2024. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.