

Camera module damper



Print Date: 2025-12-05

Benefits

- Noise reduction by adding damper into the voice coil motor with more than 20%
- Significant reduction of particle generation risk to contaminate lens
- Easier processing by overmolding versus liquid silicon rubber



Details

Arnitel® allows efficient injection moulding with 1/10 of cycle time compared with liquid silicon rubber; Arnitel has good creep resistance and wear resistance to survive cyclic impact from ceramic balls and rigid plastics in voice coil motor; Arnitel performs stable from -25°C to 100°C to prevent migration from plastics to contaminate contact surface during smartphone reliability test at high temp. high humidity, which could happens on TPU.

Products

Arnitel® EM460
TPC-ET

卖方独家声明并保证，在卖方交付之日，产品应符合商定的规格。卖方不做出任何其他明示或暗示的陈述或保证。
卖方对客户产品的设计不承担任何责任，客户有责任确定卖方的产品是安全的，符合应用法律和法规，并且在技术上或其他方面适合其预期用途。
卖方不认可或声称其产品适合特定应用，并且否认在这方面的每一项陈述或保证，无论是明示的还是暗示的。

典型值仅供参考，不应被视为具有约束力的规格。产品中的着色剂或其他添加剂可能会导致典型值发生显著变化。

版权所有 © Envalior 2025。保留所有权利。未经 Envalior 事先书面许可，不得以任何形式或任何方式复制、分发或传播信息的任何部分，包括复印、记录或其他电子或机械方法。