

Control Devices PBT HR

Automotive / Auto Electronics & Electricals

Print Date: 2024-10-15

Benefits

- Arnite PBT HR performance at elevated temperatures becomes a bridge material between commodity and speciality, which essentially fills in the performance gap without jumping to specialty prices.



Details

Arnite® PBT HR offers superior performance in mechanical property retention after environmental conditioning; Arnite PBT HR allows for design flexibility with regards to geometry, wall thickness, locking arm features and sealing types; Arnite PBT HR has a cost advantage due to its properties

Products

Arnite® TV4 261 HR-HS
PBT-GF30

Speciality products

Arnite® T

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.
Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envalior 2024. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.