

Cylinder head cover for 2-wheelers

Transportation / 2Wheelers

Print Date: 2024-03-14

Benefits

- The Cylinder head cover has to seal the engine oil and air between the engine room and cylinder head. However, in the case of a 2wheel, they are often connected by 2 to 4 bolts where a rubber gasket is used. The rubber gasket has a high reaction force so flange of the cylinder head often leaks out between the cylinder head and the head cover.

Details

Akulon® K224-HG6 results in reduction of molding time because the molding flow of Akulon is better than competitor grades; Akulon offers high creep

Products

Akulon® K224-HG6
PA6-GF30

Speciality products

Akulon®

All the trademarks mentioned here are trademarks of Envalior.

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.

Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envalior 2024. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.