

E—Motors for Power Tools

Consumer goods / Power tools

Print Date: 2025–12–05

Benefits

- Current e—motor applications are packed tight with little to no room to gain additional power or improve efficiency. With Stanyl® PA46, you can mold thinner walls (i.e., lamina stack insulation) down to .25 mm or less, allowing more room for copper windings or thicker gauge to maximize torque potential and reduce resistance.
- At high loads, e—motors generate substantial heat. Temperatures can easily exceed 150°C (302°F), resulting in mechanical failures. Stanyl® PA46 offers excellent high temperature mechanical performance with a heat deflection temperature of 290°C (554°F) and a continuous use temperature of 170°C (338°F).
- The superior flow and high crystallinity of Stanyl® PA46 results in strong and flexible weld lines, improving manufacturing yield by eliminating process scrap in rotors and stators.



Details

Stanyl® is the first high—temperature polyamide and the only aliphatic polyamide in its class. With a melting temperature of 295°C, its high crystallinity and fast crystallization speeds provide excellent high—temperature mechanical performance, superior wear and friction properties and superior flow. Stanyl® PA46 has an excellent track record in high—performance parts due to its superior strength and fatigue resistance properties, especially at high temperatures. This material is uniquely positioned in that it can be used to achieve nearly transparent thin wall moldings. For applications such as e—motors, this can free up space for compact designs (i.e., allowing higher torque ratios to maximize the performance of e—motors).

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.

Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envallor 2025. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envallor.

E-Motors for Power Tools

Consumer goods / Power tools

Products

Stanyl® 46HF5040
PA46-GF40 FR(17)

Stanyl® HFX31S
PA46-GF20 FR(40)

Stanyl® HFX61S
PA46-GF35 FR(40)

Stanyl® HFX33S
PA46-GF20 FR(40)

Stanyl® TW241F12
PA46-GF60

Stanyl® 46HF4530
PA46-GF30

Stanyl® 46HF4540
PA46-GF40

Stanyl® 46HF4550
PA46-GF50

Stanyl® HFX63S
PA46-GF35 FR(40)

Speciality products

Stanyl®



Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.
Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envalior 2025. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.