

# E-Motors for Power Tools



Print Date: 2024-07-02

## Benefits

- Current e-motor applications are packed tight with little to no room to gain additional power or improve efficiency. With Stanyl® PA46, you can mold thinner walls (i.e., lamina stack insulation) down to .25 mm or less, allowing more room for copper windings or thicker gauge to maximize torque potential and reduce resistance.
- At high loads, e-motors generate substantial heat. Temperatures can easily exceed 150°C (302°F), resulting in mechanical failures. Stanyl® PA46 offers excellent high temperature mechanical performance with a heat deflection temperature of 290°C (554°F) and a continuous use temperature of 170°C (338°F).
- The superior flow and high crystallinity of Stanyl® PA46 results in strong and flexible weld lines, improving manufacturing yield by eliminating process scrap in rotors and stators.



## Details

Stanyl® is the first high-temperature polyamide and the only aliphatic polyamide in its class. With a melting temperature of 295°C, its high crystallinity and fast crystallization speeds provide excellent high-temperature mechanical performance, superior wear and friction properties and superior flow. Stanyl® PA46 has an excellent track record in high-performance parts due to its superior strength and fatigue resistance properties, especially at high temperatures. This material is uniquely positioned in that it can be used to achieve nearly transparent thin wall moldings. For applications such as e-motors, this can free up space for compact designs (i.e., allowing higher torque ratios to maximize the performance of e-motors).

# E-Motors for Power Tools



## Products

Stanyl® 46HF5040  
PA46-GF40 FR(17)

Stanyl® HFX31S  
PA46-GF20 FR(40)

Stanyl® HFX61S  
PA46-GF35 FR(40)

Stanyl® HFX33S  
PA46-GF20 FR(40)

Stanyl® TW241F12  
PA46-GF60

Stanyl® 46HF4530  
PA46-GF30

Stanyl® 46HF4540  
PA46-GF40

Stanyl® 46HF4550  
PA46-GF50

Stanyl® HFX63S  
PA46-GF35 FR(40)

## Speciality products

### Stanyl®



这里提到的所有商标都是 Envalior 的商标。  
 卖方独家声明并保证，在卖方交付之日，产品应符合商定的规格。卖方不做出任何其他明示或暗示的陈述或保证。  
 卖方对客户产品的设计不承担任何责任，客户有责任确定卖方的产品是安全的，符合应用法律和法规，并且在技术上或其他方面适合其预期用途。  
 卖方不认可或声称其产品适合特定应用，并且否认在这方面的每一项陈述或保证，无论是明示的还是暗示的。

典型值仅供参考，不应被视为具有约束力的规格。产品中的着色剂或其他添加剂可能会导致典型值发生显著变化。

版权所有 © Envalior 2024。保留所有权利。未经 Envalior 事先书面许可，不得以任何形式或任何方式复制、分发或传播信息的任何部分，包括复印、记录或其他电子或机械方法。