

E-motor electric insulation

Automotive

Print Date: 2024-06-20

Benefits

- Application requirements High flow and mechanics Thermal conductive E-friendly HB/V0 ATF/Glycol resistant High HDT (wire welding) Material properties Thinsulation Typical UL1446 class H (0,36mm, 180°C) E-motor/E-car (thermal) load cycles



Details

Crack/tear free insulations; Design freedom (flow length); Max power density (TC solutions)

Products

Stanyl® TW200F6
PA46-GF30

All the trademarks mentioned here are trademarks of Envalior. Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied. Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envalior 2024. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.