

EV-charger

Automotive

Print Date: 2025-12-05

Benefits

- Dimensional stability
- UL94–V0 @0.75mm, GWI
- Extremely low moisture up-take
- Thermal shock resistivity
- High and stable dielectric strength
- Thermal oxidative resistance
- Enhances zero emission mobility of BEV



Details

Manufacturers of electric vehicle charging infrastructure are seeking to improve performance and reduce costs without compromising on aesthetics. Advanced polyamides with flame retardant (FR) additives are a popular choice for EV charging plugs, but the downsides versus additive—free materials include: poor surface appearance from UV exposure, lower mechanical performance, limited color options, and higher cost. Envalior's Akulon® PA6 and PA66 material solutions offer a superior and proven alternative to common FR materials used in EV Charging Plugs. The Akulon® family of engineering materials delivers durable, affordable and versatile performance. For peace of mind, they are also tested to meet or exceed the latest UL and IEC standards for fire and electrical safety.

Products

PA6-GF30 FR(40)

Speciality products

Enhances zero emission mobility of BEV

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.

Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with

Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.