

EV-charger



Print Date: 2024-06-20

Benefits

- Dimensional stability
- UL94-V0 @0.75mm, GWI
- Extremely low moisture up-take
- Thermal shock resistivity
- High and stable dielectric strength
- Thermal oxidative resistance
- Enhances zero emission mobility of BEV



Details

Manufacturers of electric vehicle charging infrastructure are seeking to improve performance and reduce costs without compromising on aesthetics. Advanced polyamides with flame retardant (FR) additives are a popular choice for EV charging plugs, but the downsides versus additive-free materials include: poor surface appearance from UV exposure, lower mechanical performance, limited color options, and higher cost. Envalior's Akulon® PA6 and PA66 material solutions offer a superior and proven alternative to common FR materials used in EV Charging Plugs. The Akulon® family of engineering materials delivers durable, affordable and versatile performance. For peace of mind, they are also tested to meet or exceed the latest UL and IEC standards for fire and electrical safety.

Products

Akulon® Ultraflow XG-FKGS6
PA6-GF30 FR(40)

Speciality products

Enhances zero emission mobility of BEV

这里提到的所有商标都是 Envalior 的商标。
卖方独家声明并保证，在卖方交付之日，产品应符合商定的规格。卖方不做出任何其他明示或暗示的陈述或保证。
卖方对客户产品的设计不承担任何责任，客户有责任确定卖方的产品是安全的，符合应用法律和法规，并且在技术上或其他方面适合其预期用途。
卖方不认可或声称其产品适合特定应用，并且否认在这方面的每一项陈述或保证，无论是明示的还是暗示的。

典型值仅供参考，不应被视为具有约束力的规格。产品中的着色剂或其他添加剂可能会导致典型值发生显著变化。

版权所有 © Envalior 2024。保留所有权利。未经 Envalior 事先书面许可，不得以任何形式或任何方式复制、分发或传播信息的任何部分，包括复印、记录或其他电子或机械方法。