

# Endlaminates (electro motors)

## Automotive / e-Drivetrain / HV E-motors

Print Date: 2024-11-12

### Benefits

- Reliable
- Long term high temperature resistant
- Good flowability enables thin wall designs
- Durable
- Good electrical insulation
- Creep resistant



### Details

Stanyl® PA46 is the first high-temperature polyamide and the only aliphatic polyamide in its class, making it an ideal choice for applications such as endlaminates (electro motors). Due to a high temperature resistance, Stanyl® PA46 is UL1446 class H certified. Its creep resistance at elevated temperatures, high toughness levels, and good electrical insulation properties make it a cost-effective solution. Stanyl® PA46 offers good flowability and processability that enables thin wall designs, while Xytron™ PPS allows for super high long term temperature resistance.

### Products

Stanyl® TW200F6  
PA46-GF30

Stanyl® TW341  
PA46

Stanyl® TE250F6  
PA46-GF30 FR(17)

Stanyl® TW200F8  
PA46-GF40

ForTii® F11  
PPA-GF30 FR(40)

ForTii® T11  
PPA-GF30 FR(40)

Xytron™ G3010E  
PPS-I-GF30

Xytron™ G4010T  
PPS-GF40

### Speciality products

#### Xytron™

## Endlaminates (electro motors)

Automotive / e-Drivetrain / HV E-motors



Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.  
Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envalior 2024. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.