

# Faucet system components

## Consumer goods

Print Date: 2025-12-05

### Benefits

- Application requirements High strength (static pressure > 500psi, bending strength >61Nm) No water leakage during lifetime (cycle test up to 1 million cycles) High crew thread strength Material properties Superior stiffness and toughness Good hydrolysis resistance High dimensional stability All major drinking water approvals



### Details

Lead-free solution; Due to outstanding performance, lower risk of part failure and water leakage; Bio-based polymer

### Products

EcoPaXX® Q-DWX10  
PA410-GF50

Xytron™ G3010E  
PPS-I-GF30

Xytron™ G4020DW-FC  
PPS-GF40

ForTii® WX12-FC  
PPA-GF40

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.  
Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envallor 2025. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envallor.