Filter box

Consumer goods | Household utensils

Benefits

 The filter box in an automatic coffee machine is used to filtrate and collect the coffee bean fragment and skin during grinding process after fresh bean baking. Hence the air take out of those fragments will be hot (around 130C during the the process), which results the part to suffer from high temperature.

Print Date: 2024-11-12

Xytron™ offers excellent dimensional stability after molding and shows low creep during the heat age test; Xytron™ is able to withstand long term heat testing at 130C and shows little change of mechanical properties; Xytron™ provides provide low smell 8 emission during the roasting of the coffee bean, which ensure the coffee tastes well after the brewing process; Material has a metal feel to it when touched

Products

Details

Speciality products

Xutron™

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied. Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical

Copyright © Envalior 2024. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.



