

# Fuel tank PHEV

## Automotive

Print Date: 2024-08-30

### Benefits

- Low Fuel permeation
- Cold impact resistance



### Details

As the hybrid vehicle market increases, reducing the complexity of the hybrid fuel tank is key to manufacturers. Using advanced polyamides can reduce the complexity of producing these tanks and create cost savings, thus, you can gain a competitive advantage through greater efficiency and potential cost-savings. At Envalior Engineering Materials, we offer Fuel Lock Technology—an effective and proven solution for superior hybrid fuel tanks. Offering excellent barrier properties in a monolayer material, Fuel Lock Technology offers weight reduction and less post-processing via an injection molding process. Compared to HDPE/EVOH material used for blowmolded tanks, it can combine good mechanical properties and barrier performance in one material. Processing the material by means of plastic injection molding offers the design freedom to apply local reinforcements, make optimal use of the available building space and integrate functional features. Additionally, no secondary operations are needed because features like baffles and pillars are designed into the tank and injection molded together with the fuel tank body.

### Products

Akulon® Fuel Lock FL40-HPX2  
PA6-I

All the trademarks mentioned here are trademarks of Envalior.

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.

Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envalior 2024. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.