

High voltage connector e–motor

Automotive

Print Date: 2025–12–05

Benefits

- Application requirements Electrical insulation High CTI 600 V UL94 V0 halogen–free Thermal cycles/shock resistant Material properties Low moisture uptake Chemical resistant Thermal cycles/fatigue Electric insulative



Details

Robust (wire load) design; Harsh environment; Improved lifetime/safety vs PA66/PBT

Products

ForTii® F11
PPA–GF30 FR(40)

Akulon® SG–KGS6/HV
PA66–GF30 FR(40)

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.
Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envallor 2025. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envallor.