

High voltage connector

Automotive

Print Date: 2025-12-05

Benefits

- Application requirements Superior electrical performance Dedicated high voltage High mechanical strength Material properties CTI 600V, RTI 140°C Halogen-free UL94-V0 @ 0.75mm Superior processability



Details

High mechanical strength; Orange color; Excellent electrical performance enabling high safety and reliability; Lowest tool downtimes

Products

ForTii® T11
PPA-GF30 FR(40)

ForTii® TX1
PPA-GF30 FR(40)

Akulon® SG-KGS5/HV
PA66-GF25 FR(40)

Akulon® SG-KGS6/HV
PA66-GF30 FR(40)

Durethan® BKV30FN04
PA6-GF30 FR(40)

Durethan® BKV45FN04
PA6-GF45 FR(40)

Pocan® BFN4232HR
PBT-GF25 FR(40)

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.

Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envalior 2025. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.