

# High-temperature automotive connectors

## Automotive | Auto Electronics & Electricals | Connectors

Print Date: 2024-08-30

### **Benefits**

· W2W: PBT, PA6, PA66, PA46 Standard: PA66, PA46, PA6, PBT Reflow: PA46, PA4T



#### Details

Stanyl® PA46, ForTii® PA4T, EcoPaXX® PA410, Akulon® PA66, Akulon® PA6, Arnite® PBT allow for reliable solutions due to high temperature resistance, high mechanical property levels and good electrical insulation properties; Akulon® PA6 and PA66 allow for cost effective solutions due to high mechanical properties (especially toughness and strength)

#### **Products**



All the trademarks mentioned here are trademarks of Envalior.
Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.
Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical