

Hydrogen fuel cells



Print Date: 2024-11-12

Benefits

- Fuel cell systems need to use materials that are pure. If not, ion leaching will occur which will poison the catalyst & clog the membrane, lead to life time & efficiency drop of fuel cell system
- Moreover, material with excellent hydrolytic and heat aging resistance is highly favorable to ensure its life time performance. Xytron™, our high-performance PPS compound, offers the high purity and superior mechanical performance needed to achieve the industry's lowest ion leaching performance at temperatures up to 120°C, and highest hydrolytic and chemical resistance. This enables OEMs to develop long-lasting, highly efficient PEMFCs that lower the cost per kilometer and total cost of ownership for end users.



Details

Lowest ion leaching of its kind, up to 120°C; Best strength and toughness retention in hydrolytic environment; Best dimensional stability, fatigue and creep resistance; Best weldline strength before and after hydrolytic and heat aging

Products

Xytron™ G4020DW-FC
PPS-GF40

Xytron™ G4080HR
PPS-GF40

Speciality products

Xytron™

卖方独家声明并保证，在卖方交付之日，产品应符合商定的规格。卖方不做出任何其他明示或暗示的陈述或保证。卖方对客户产品的设计不承担任何责任，客户有责任确定卖方的产品是安全的，符合应用法律和法规，并且在技术上或其他方面适合其预期用途。卖方不认可或声称其产品适合特定应用，并且否认在这方面的每一项陈述或保证，无论是明示的还是暗示的。

典型值仅供参考，不应被视为具有约束力的规格。产品中的着色剂或其他添加剂可能会导致典型值发生变化。

版权所有 © Envalior 2024。保留所有权利。未经 Envalior 事先书面许可，不得以任何形式或任何方式复制、分发或传播信息的任何部分，包括复印、记录或其他电子或机械方法。