

Internal structure for mini projector

Consumer goods | Appliances

Print Date: 2024-11-12

Benefits

- Xytron G4012T—the 40%GF reinforce PPS which is Halogen-free. In addition, there is low outgassing in the test at 100C for 48h and 10 cycles

Details

Xytron™ offers excellent toughness and weld line strength property, the material is able to do the drop test in 1.5M with no buckle break; Xytron offers good dimension stability and low warpage; Xytron allows for low smelling after 48H of continuous work; Xytron fulfills low halogen requirement (<900ppm); Xytron allows good processing & low flash

Products

Xytron™ G4012T
PPS-GF40

Speciality products

Xytron™

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.
Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envalior 2024. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.