

MCCB Housings

Electrical | Power distribution | Low Voltage Switchgear

Print Date: 2024-06-20

Benefits

- Most grades are available with halogenfree flameretardancy, and in specific electro-grey colour for housings. ForTii® Heat Deflection Temperature (HDT) of 305°C .



Details

Akulon® PA6 and ForTii® PA4T enable increased design flexibility and integrated functionality, facilitating smart assembly solutions; Akulon® PA6 and ForTii® PA4T allow for reliable solutions due to good dielectric aging performance at 150°C and high CTI values at 600 Volts; Akulon® PA6 and ForTii® PA4T allow for potential system cost reductions up to 15% (wall thicknesses reduced leading to a volume reduction of up to 25%) compared to conventional materials

Products

ForTii® F11
PPA-GF30 FR(40)

ForTii® F12
PPA-GF40 FR(40)

Akulon® SG-KGS6
PA66-GF30 FR(40)

Akulon® Ultraflow XG-FKGS6
PA6-GF30 FR(40)

All the trademarks mentioned here are trademarks of Envalior.
Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.
Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envalior 2024. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.