

# Medical Packaging Blown Film

## Healthcare | Medical Devices and Accessories

Print Date: 2024-04-12

### Benefits

- The very high viscous Akulon® F136 range is suitable for blown film. This range contains grades with lubrication, nucleation agent or a combination of those. Good sterilization properties are mandatory in the world of Medical Instrument Packaging. The Akulon® PA6 grades fulfil all required needs, including the good oxygen barrier properties.



### Details

Akulon® PA6 has an outstanding mechanical strength; Akulon® has good oxygen barrier properties

### Products

Akulon® F136  
PA6

Akulon® F136-C1  
PA6

Akulon® F136-E1  
PA6

Akulon® F136-E2  
PA6

Akulon® F136-C  
PA6

### Speciality products

#### Akulon® F



All the trademarks mentioned here are trademarks of Envalior.

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.

Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envalior 2024. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.