

Radiator End Caps

Automotive / Engine / Cooling / Thermal management

Print Date: 2024-08-30

Benefits

- Cost-effective
- Heat-stabilized
- Enhanced hydrolytic stability



Details

Akulon® PA66 HR is a reliable solution for radiator end caps due to its excellent hydrolysis resistance and good thermomechanical properties. It allows for lightweight solutions (10% lighter compared to PPS). Akulon PA66 HR HG7 has very good resistance to glycol/water mixtures used at high temperatures in automotive cooling systems. New materials used in cooling systems are required to have a flexural strength of at least 20 N/mm² after emersion in a ethylene glycol solution for one thousand hours at 135°C (275°F).

Products

Akulon® HR-HG7
PA66-GF35



All the trademarks mentioned here are trademarks of Envalior.
Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.
Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envalior 2024. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.