

# Relay Bases

## Electrical | Electrical Components

Print Date: 2024-08-30

### Benefits

- This application is used in computer or electrical products. This application is used for signalling or power turn on or off.



### Details

Stanyl® PA46 allows for reliable solutions due to good mechanical properties at low and elevated temperatures, HDT 290°C suitable thus for SMT, excellent CTI values and arc resistance values, UL146 class F (unreinforced) and class H (reinforced grades); Stanyl® PA46 allows for cost effective solutions due to much shorter molding cycle times as compared to most competitive materials

### Products

Stanyl® TS250F8  
PA46-GF40 FR(17)



All the trademarks mentioned here are trademarks of Envalior.  
Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.  
Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envalior 2024. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.