

Variator transmission parts

Transportation | 2Wheelers

Print Date: 2024-06-20

Benefits

- Excellent resistance to wear
- Chemical-resistant to automotive fluids
- Heat-resistance for variator cover rollers
- Retains its mechanical properties at temperatures ranging from 100°C (212°F) to 170°C (338°F)
- Exceptional fatigue properties to meet demanding durability requirements



Details

Stanyl® PA46 is a reliable solution for variator transmission parts since it extends part lifetime up to 200% compared to conventional material — due to its proven wear and high chemical resistance. Stanyl TW341 demonstrates proven performance up to 6,000 km (3,728 miles), whereas PA6 and PA66 deliver up to 3000 km (1,864 miles) for this application.

Products

Stanyl® TW341
PA46

Speciality products

Stanyl®

All the trademarks mentioned here are trademarks of Envalior.
Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.
Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envalior 2024. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.