

Water pump part

Industrial equipment / Pumps & valves

Print Date: 2025-12-05

Benefits

- This fin part is assembled with the impeller part (metal) inside the water pump. Furthermore, the dimensional stability and high rigidity and strength of Xytron are essential in this application.

Details

Xytron™ offers high rigidity and strength; Xytron offers good heat aging resistance in continuous service temperature; Xytron has good dimensional stability; Xytron has very good hydrolysis resistance

Products

Xytron™ G4010T
PPS-GF40

Xytron™ G4024T
PPS-GF40

Xytron™ M6510A
PPS-(GF+MD)65

Speciality products

Xytron™

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.
Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envallor 2025. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envallor.