

# Tepex<sup>®</sup> dynalite 207–C200(x)/50%

## PPS–CF58

Print Date: 2024–06–15

**Tepex<sup>®</sup> dynalite 207–C200(x)/50%**  
 3K Carbon – PPS consolidated composite laminate

**Tepex<sup>®</sup>**  
**BOND**  
**LAMINATES**  
 A company of Envalior

The datasheet is valid for this specific composition only, the characteristics of composites depend on reinforcement level and fiber orientation. Non–standard thickness may alter some or all of these properties. The data listed here are given as average product properties and should not be used to establish specification limits nor used alone as basis of design. The underlying tests were conducted at room temperature and (where possible) with 2 mm specimen thickness. For tensile and flexural tests a specimen width of 25 mm was used and is highly recommended to achieve representative results.

PROPERTIES	TYPICAL DATA	UNIT	TEST METHOD
<b>LAYUP</b>	<b>VALUE</b>		
Fiber	3K Carbon		
Weaving style	Twill 2/2		DIN ISO 9354
Area weight (dry fabric)	200	g/m <sup>2</sup>	DIN EN 12127
Weight rate (0°/90°)	50/50	%/%	
Fiber volume content	50	vol.-%	nominal
Thickness per layer	0.22	mm	nominal

### MECHANICAL PROPERTIES

DRY / COND

Tensile Modulus	52 / –	GPa	ISO 527–4/5
Tensile Strength	750 / –	MPa	ISO 527–4/5
Elongation at Break	1.3 / –	%	ISO 527–4/5
Flexural Modulus	46 / –	GPa	ISO 14125
Flexural Strength	830 / –	MPa	ISO 14125

### THERMAL PROPERTIES

DRY / COND

All the trademarks mentioned here are trademarks of Envalior.  
 Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.  
 Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.  
 Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.  
 Copyright © Envalior 2024. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.

## Property Data

# Tepex<sup>®</sup> dynalite 207–C200(x)/50%

Print Date: 2024–06–15

PROPERTIES	TYPICAL DATA	UNIT	TEST METHOD
Density	1560 / –	kg/m <sup>3</sup>	ISO 1183
Glass transition temperature (10°C/min)	91 / *	°C	ISO 11357–1/–2
Melting temperature (10°C/min)	280 / *	°C	ISO 11357–1/–3
Heat deflection temperature (0.1% flex. Modulus)	270	°C	ISO 75–1/3
Burning Behav. at 1.5 mm nom. thickn.	V–0 / *	class	IEC 60695–11–10
Thickness tested	1.5 / *	mm	IEC 60695–11–10
Burning Behav. at 3.0 mm nom. thickn.	V–0 / *	class	IEC 60695–11–10
Thickness tested	3 / *	mm	IEC 60695–11–10
Burning Behav. at 0.4 mm nom. thickn.	V–0 / *	class	IEC 60695–11–10
Thickness tested	0.4 / *	mm	IEC 60695–11–10
Burning Behav. at 0.75 mm nom. thickn.	V–0 / *	class	IEC 60695–11–10
Thickness tested	0.75 / *	mm	IEC 60695–11–10
CLTE –35°C to 23°C (0°)	3.8	E–4/°C	ISO 11359–1/–2
CLTE 23°C to 80°C (0°)	3.7	E–4/°C	ISO 11359–1/–2

All the trademarks mentioned here are trademarks of Envalior.

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied.

Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values.

Copyright © Envalior 2024. All rights reserved. No part of the information may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of Envalior.